

XM7-26W LCD Color display monitor Specification Sheet

Features

26"W a-Si TFT active matrix
 Friendly OSD User controls
 Plug & Play Capability
 HDCP Function
 Color Enhance
 With protective glass



Detailed Specifications

LCD PANEL

Display area (H x V)	550.08(H) x 343.8(V) mm (26" diagonal)
Viewing angle (typ.)	170° (H) / 150° (V) (CR >=10)
Pixel pitch (H x V)	0.2865x 0.2865 mm
Resolution (max.)	1920x1200 @ 60Hz
Response time (typ.)	5 ms
Luminance of white (typ.)	450 cd/m ²
Contrast ratio (typ.)	750: 1(Dynamic 3000:1)

Electrical Features

Horizontal frequency	30~ 81 KHz
Vertical frequency	60 ~ 75 Hz
Maximum resolution	1920x1200 @ 60 Hz
Number of color	16.7M
Input signal	0.7 Vpp / 75 ohms
Syns signal (TTL level)	LH: 2.0 ~ 5.0 Vpp, LL: 0 ~ 0.8 Vpp
Input voltage	AC 100 ~ 240 V / 50 ~ 60 Hz
Power consumption	100 watts (max.)
Power Savings	<2 watts (off mode)
Power supply type	Integrated

User Controls

Control type	OSD / 5keys
Menu functions	Contrast / Brightness: Contrast / Brightness Image adjust: H-position/V-position/phase Audio: Volume Colour : 6500K/9300K OSD Setup : Language/OSD H-position/V-position/ Reset : Factory Recall
OSD Language	16 languages (Eng/Deu/Fre/Ita/Spa/Por/Ch-s/Ch-t/Pol/Rus/Kor /Dan/Dut/Fin/Swe/Jap)
Messages of OSD	Self test Power saving Over frequency range

Regulatory Compliance

Plug & Play	VESA® DDC1/2B
Power management	VESA® DPMS
Ergonomics & Environmental	RoHS,WEEE
EMC & Safety	FCC,CE,CB,
Video standard	VESA, VGA, DVI, HDMI
Wall Mounts	VESA® FPMPI standard 100mm x 100mm

Connections

AC in	AC 100 ~ 240 V / 50 ~ 60 Hz
VGA	D-sub x1, 15 pin--- detachable,
DVI	Yes, detachable
HDMI	Yes
Audio in	Yes
Audio out	No

AV in	No
TV in	No

Mechanical & Physical Features

Unit Dimension (W x H x D)	613.2 mm x 472.5 mm x 218.9 mm
Weight (Net / Gross)	8.3/9.6 kg
Swivel (L/R)	No
Tilt (up/down)	+25° / -5°
Rotation (F/R)	No

Accessory

Signal cable	15 pin mini D-sub (comply PC99)/DVI-D/HDMI(optional)
Power cord	150 cm
Audio cable	150 cm(optional)
Manual	6 languages
Quick Guide	Yes
Warranty Card	1 year

Packing Specification

Packing Dimension (W x H x D)	680mm x 540mm x 204mm
Container Load (20ft/40ft)	20ft w/ pallet: 264 units 40ft w/ pallet: 558 units

Multimedia feature

Speaker	3W x2 ,with amplifier
---------	-----------------------

Specifications subject to change without prior notice

PROVIEW TECHNOLOGY (SHENZHEN) CO., LTD. TEL.: +86-755-25261512 FAX.: +86-755-25261565 [http:// www.proview.com.cn](http://www.proview.com.cn)